



Appendix A

GLOSSARY / ABBREVIATIONS

GLOSSARY

Included in the following pages are a number of terms with appropriate definitions to assist the reader in understanding the technical language included in this document.

Air carrier: an operator which: (1) performs at least five round trips per week between two or more points and publish flight schedules which specify the times, days of the week and places between which such flights are performed; or (2) transport mail by air pursuant to a current contract with the U.S. Postal Service. Certified in accordance with Federal Aviation Regulation (FAR) Parts 121 and 127.

Air Taxi: An air carrier certificated in accordance with FAR Part 135 and authorized to provide, on demand, public transportation of persons and property by aircraft. Generally operates small aircraft "for hire" for specific trips.

Airport Reference Code (ARC): A coding system used to relate airport design criteria to the operational and physical characteristics of the airplanes expected to operate at the airport.

Airport Traffic Control Tower (ATCT): a central operations facility in the terminal air traffic control system, consisting of a tower, including an associated IFR room if radar equipped, using air/ground communications and/or radar, visual signaling and other devices, to provide safe and expeditious movement of terminal air traffic.

Air Route Traffic Control Center (ARTCC): a facility established to provide air traffic control service to aircraft operating on an IFR flight plan within controlled airspace and principally during the enroute phase of flight.

Approach Lighting System (ALS): an airport lighting facility which provides visual guidance to landing aircraft by radiating light beams by which the pilot aligns the aircraft with the extended centerline of the runway on his final approach and landing.

Azimuth: horizontal direction or bearing; usually measured from the reference point of 0 degrees clockwise through 360 degrees.

Base leg: a flight path at right angles to the landing runway off its approach end. The base leg normally extends from the downwind leg to the intersection of the extended runway centerline.

Compass locator (LOM LMM): a low power low/medium frequency radio-beacon installed in conjunction with the instrument landing system at one or two of the marker sites.

Control zone: airspace extending upward from the ground which may include one or more airports and is normally a circular area of five statute miles in radius with extensions, where necessary, to include instrument approach and departure paths.

Displaced threshold: a threshold that is located at a point on the runway other than the designated beginning of the runway.

Distance Measuring Equipment (DME): equipment (airborne and ground) used to measure, in nautical miles, the slant range distance of an aircraft from the DME navigational aid.

DNL: day-night noise level. The daily average noise metric in which that noise occurring between 10:00 p.m. and 7:00 a.m. is penalized by 10 times.

Downwind leg: A flight path parallel to the landing runway in the direction *opposite* the landing direction.

Duration: length of time, in seconds, a noise event such as an aircraft flyover is experienced. (May refer to the length of time a noise event exceeds a specified threshold level.)

Enplaned passengers: the total number of revenue passengers boarding aircraft, including originating, stop-over, and transfer passengers, in scheduled and non-scheduled airlines.

Fixed Base Operator (FBO): a provider of service to users of an airport. Such services include, but are not limited to, fueling, hangaring, flight training, repair and maintenance.

General aviation (GA): that portion of civil aviation which encompasses all facets of aviation except air carriers holding a Certificate of Convenience and Necessity, large aircraft commercial operators military aircraft.

Glide slope: electrical equipment that emits signals which provide vertical guidance by reference to airborne instruments during instrument approaches such as an ILS, or visual ground aids, such as VASI, which provide vertical guidance for a VFR approach or for the visual portion of an instrument approach and landing.

Global Positioning Satellite System (GPS): a navigational system utilizing satellites to provide non-precision guidance in azimuth, elevation, and distance measurement.

Ground effect: the excess attenuation attributed to absorption or reflection of noise by man-made or natural features on the ground surface.

Instrument approach: a series of predetermined maneuvers for the orderly transfer of an aircraft under instrument flight conditions from the beginning of the initial approach to a landing, or to a point from which a landing may be made visually. It is prescribed and approved for a specific airport by competent authority.

Instrument Flight Rules (IFR): rules governing the procedures for conducting instrument flight. Also a term used by pilots and controllers to indicate type of flight plan.

Instrument Landing System (ILS): a precision instrument approach system which normally consists of the following electronic components and visual aids: localizer, glide slope, outer marker, middle market, and approach lights.

Localizer (LOC): providing horizontal guidance to the runway centerline for aircraft during approach and landing by radiating a directional pattern of radio waves modulated by two signals which, when received with equal intensity, are displayed by compatible airborne equipment as an "on-course" indication, and when received in unequal intensity are displayed as an "off-course" indication.

Localizer type directional aid (LDA): a facility of comparable utility and accuracy to a localizer, but is not part of a complete ILS and is not aligned with the runway.

Missed approach: an instrument approach not completed by landing. This may be due to visual contact not established at authorized minimums or instructions from air traffic control, or other reasons.

Non-directional beacon (NDB): a radio beacon transmitting non-directional signals that a pilot of an aircraft equipped with direction finding equipment can determine his/her bearing to or from the radio beacon and "home" on or track to or from the station. When the radio beacon is installed in conjunction with the Instrument Landing System market, it is normally called a Compass Locator.

Nonprecision approach procedure: a standard instrument approach procedure in which no electronic glide slope is provided, such as VOR, TACAN, GPS, NDB, or LOC.

Operation: a take-off or a landing.

Outer marker (OM): an ILS navigation facility in the terminal area navigation system located four to seven miles from the runway edge on the extended centerline indicating to the pilot, that he/she is passing over the facility and can begin final approach.

Poor Visibility Condition (PVC): Weather conditions whenever cloud ceiling is less than 500 feet and/or visibility is less than one statute mile.

Precision Approach Path Indicator (PAPI): an airport lighting facility in the terminal area navigation system used primarily under VFR conditions. The PAPI provides visual descent guidance to aircraft on approach to landing through a single row of two to four lights, radiating a high intensity red or white beam to indicate whether the pilot is above or below the required approach path to the runway. The PAPI has an effective visual range of 5 miles during the day and 20 miles at night.

Precision approach procedure: a standard instrument approach procedure in which an electronic glide slope is provided, such as ILS. GPS precision approach may be provided in the future.

Precision instrument runway: a runway having a existing Instrument Landing System (ILS).

Reliever Airport: an airport to serve general aviation aircraft which might otherwise use a congested air carrier served airport.

Special VFR (SVFR): Weather conditions less than VFR, but greater than IFR. SVFR operations can only be conducted if approved by the controlling ATC facility.

Vector: a heading issued to a pilot to provide navigational guidance by radar.

Victor airway: a control area or portion thereof established in the form of a corridor, the centerline of which is defined by VOR's.

Visual approach: an approach wherein an aircraft on an IFR flight plan, operating in VFR conditions under the control of an air traffic facility and having an air traffic control authorization, may proceed to the airport of destination in VFR conditions.

Visual approach slope indicator (VASI): an airport lighting facility in the terminal area navigation system used primarily under VFR conditions. It provides vertical visual guidance to aircraft during approach and landing, by radiating a pattern of high intensity red and white focused light beams which indicate to the pilot that he/she is above, on, or below the glide path.

Visual Flight Rules (VFR): rules that govern the procedures for conducting flight under visual conditions. The term VFR is also used in the United States to indicate weather conditions that are equal to or greater than minimum VFR requirements. In addition, it is used by pilots and controllers to indicate type of flight plan.

Very High Frequency Omnidirectional Range Station (VOR): a ground-based electronic navigation aid transmitting very high frequency navigation signals, 360 degrees in azimuth, oriented from magnetic north. Used as the basis for navigation in the national airspace system. The VOR periodically identifies itself by Morse Code and may have an additional voice identification feature.

Very High Frequency Omnidirectional Range/Tactical Air Navigation (VORTAC): a navigation aid providing VOR azimuth, TACAN azimuth, and TACAN distance-measuring equipment (DME) at one site.

ABBREVIATIONS

AGL:	above ground level
AIP:	airport improvement program
ALP:	airport layout plan
ALS:	approach lighting system
ARFF:	airport rescue and firefighting
ARTCC:	air route traffic control center
ASOS:	automated surface observing system
ATCT:	airport traffic control tower
AWOS:	automated weather observing system
CIP:	capital improvement program
DME:	distance measuring equipment
DNL:	average yearly day-night sound level
DWL:	runway weight bearing capacity for aircraft with dual-wheel type landing gear
DTWL:	runway weight bearing capacity for aircraft with dual-tandem type landing gear
FAA:	Federal Aviation Administration
F.A.R.:	Federal Aviation Regulations
FBO:	fixed base operator
GPS:	global positioning satellite system
GS:	glide slope
IFR:	instrument flight rules (F.A.R. Part 91)
ILS:	instrument landing system

LMM: compass locator at middle marker

LOC: ILS localizer

LOM: compass locator at outer marker

MIRL: medium intensity runway lights

MITL: medium intensity taxiway lights

MM: middle marker

MSL: mean sea level

NAVAID: navigational aid

NDB: non-directional beacon

NM: nautical mile

OM: outer marker

PAPI: precision approach path indicator

PVC: poor visibility condition

REIL: runway end identifier lights

SEL: sound exposure level

SVFR: special visual flight rules

SWL: runway weight bearing capacity for aircraft with single-wheel type landing gear

TACAN: tactical air navigation system

TRACON: terminal radar approach control

UHF: ultra high frequency

VASI: visual approach slope indicator

VFR: visual flight rules (F.A.R. Part 91)

VHF: very high frequency

VOR: very high frequency omnidirectional range

VORTAC: (see VOR and TACAN)